Sales Director: Darcy
Whatsapp: 008613425174299
Email: Darcy@szledworld.com

LED WORLD
www.szledworld.com

Rental indoor led display (512x512cabinet)

Features:

- ○ High resolution high precision;
- ○ Seamless splicing,High gray scale, good Performance
- ○ Fanless design
- ○ Large view angle
- ○ The most effective solution for indoor HD Billboard.
- ○ With fast locks,easy to install and Dismantle
- ○ Light weight:about 6.5kg/cabinet

Cabinet 1

Cabinet 2

| Eveaness | Noiseless | Beautiful | Good ventilation | Ultra-light | Easy installation |

Application:

○ Stage Performance   ○ Conference   ○ Celebration   ○ banquet   ○ exhibition

Technical Specifications:

Pixel pitch	2.0mm
Pixel Configuration	1R1G1B
LED component	SMD1010
Size of module	256mm x 128mm
Resolution of module	128x64
Size of cabinet	512mm x 512mm x 78mm
Resolution of cabinet	256x256
Material of Cabinet	Die-casting Aluminum
Weight of Cabinet	About 6.5KG/cabinet
Brightness	1000cd/sq.m
Density	250000dots/sq.m
Best viewing angle	140 /140
Best viewing distance	1.5-20M
Maximum power consumption	600W/sq.m
Average power consumption	300W/sq.m
Driving method	1/32 scan
Control method	Synchronization
Gray scale	65536
Colors	256*256*256
Working voltage	AC220V/110V±10%
Working temperature	-20ºC~+50ºC ±10%
Working humidity	10% ~ 90%
MTBF	10,000 hours
Frame frequence	50/60Hz
Refresh frequence	>3000Hz
IP grade	IP31
Life Span	100,000 hours
Data transafer method	RJ45
Accepting signal with video processor	PAL/NTSC/SECAM,S-Video;VGA;RGB;HDMI,DVI,Composite Video;SDI,DP etc.
Systems operating platform	WINDOWS(WINXP,WIN7/8/10), and interfaces for secondary development
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to Led World.	